



1.8m x 1.8m MULTI MAT CRANE OUTRIGGER SYSTEM

**Twenty Individual Mats = 0.6m x 1.8m
 With a 3.24m Coverage Area**



NEED ADVICE?
 We have experienced staff who can help you. We can visit your site to discuss your needs.
+44 (0) 1902 405553

Length 1.8m

Width 1.8m

**Delivered By Transport and Individually
 Lifted into Position by Two people or onsite forklift**

- Fully Certified
- 20 individual mats per set
- Length 1.8m
- Width 0.6m
- Thickness 50mm
- Max Individual mat weight = 50kg
- Max Point Load = 140,000kg

Applications

- ✓ Crane Outriggers
- ✓ Scissor Lifts
- ✓ Concrete Pumps
- ✓ MEWPS





MULTI MAT SYSTEM

CONFIGURATION OPTIONS

1800mm

**ORIGINAL
MULTI MAT**



2.16m² Configuration

Requires:
IP-57710 x 2
IP-57685 /IP-57673
(Optional)



3.24m² Configuration

Requires:
IP-57710 x 5
IP-57685 /IP-57673
(Optional)



The Multi Mat system has been tested and approved by Lloyds British.

NEED ADVICE?

We have experienced staff who can help you. We can visit your site to discuss your needs.

+44 (0) 1902 405553

MULTI MAT SET-UP

STAGE 1



Position the first level of Multi Mat system

STAGE 2



Place the second level on top at 90 degrees

STAGE 3



Add a circular pad or square pad on top to secure